

EXAMPLES OF POSSIBLE ARRANGEMENT

CONSECUTIVE	DUPLICATE	ALPHA/SYMBOLS
99998	185701	AB8724
99999	185701	CPT-57
100000	185702	612-87
100001	185702	D/8 -01
PREFIX/SUFFIX, LOGO OR TYPES		
<i>Bradma</i> 409768	102875	BRADMA
<i>Bradma</i> 409769	102876	BRADMA

Prefix does not change Serial nos. change

Standard Bradma Diehard AUTOMATIC ROTARY NUMERATORS have **six wheels** and come in the following sizes :

Size mm	Code	Character Pitch (mm)	Actual Size	Length of impression with 6 wheels (mm)
1.6	6AN062	2.50	2 3 4 5 6 7	13.5
2	6AN020	2.90	2 3 4 5 6 7	15.7
3	6AN030	4.32	2 3 4 5 6 7	23.4
4	6AN040	4.58	2 3 4 5 6 7	24.5

ALSO AVAILABLE, ON SPECIAL ORDER :

- Special sizes of 5mm and 6mm.
- Concave character faces (for bicycle frames, etc.)
- Special calligraphy
- Custom-built numerators with more than 6 wheels.
- Prefix/Suffix types or logo - to accompany variable data.
- Numerators made of special metals to withstand red-hot temperatures.

- Wheels made from special tool steel.
- Advancing cams machined into solid wheels. Cam material as durable as stamping characters.
- Extra wide unit wheel for longer life.
- One-piece actuating pawl machined from solid.
- Direct-reading characters to check set-up.
- No rivetted assembly - easy to dismantle and clean by user.
- Holding catch and springs of unique design.

Standard shank 25mm dia x 35mm length. Can be easily changed for another size.